ALUMINUM TERMINALS

TYPE ASXR/ASXR 2

Straight Bolted
Cable or Pipe to Flat Pad

Aluminum bolted terminal for aluminum cable or pipe to flat, straight or 90°.

Casting Alloy: 356-T6 Aluminum
Clamping Hardware: Aluminum Alloy




FIG. 1




FIG. 2




FIG. 3

CATALOG NUMBER	FIG. NO.	CONDUCTOR RANGE		DIMENSIONS - INCHES			WEIGHT (POUNDS)
		CABLE	NPS	L	W	S	
ASXR-48	1	#2 - 2000 MCM	3/8 - 1	3-3/8	3-3/8	2-1/4	2.35
ASXR2-48-NW	2	(2) #2 - 2000 MCM	3/8 - 1	3-3/8	3-3/8	2-1/4	4.10
ASXR2-48	3	(2) #2 - 2000 MCM	3/8 - 1	3-3/8	3-3/8	2-1/4	4.10

TYPE FNXR-AL

Dual Function
Tee Connector/Terminal
Cable or Pipe

Aluminum bolted, dual function Tee/Terminal for cable or pipe connections to flat pad tap. Reversible cap allows a wide range conductor, straight or 90° to a 2 or 4 hole NEMA flat.

Casting Alloy: 356-T6 Aluminum
Clamping Hardware: Aluminum Alloy




FIG. 1




FIG. 2

CAP MAY BE TURNED OR REVERSED TO CLAMP CONDUCTOR WITHIN RANGE SHOWN.

CATALOG NUMBER	FIG. NO.	W	T	CONDUCTOR RANGE	
				CABLE	NPS
FNXR-0139-2B-AL	2	2	1/2	#8 - 1300 MCM	1/4 - 1
FNXR-0139-4A-AL	1	3	3/8	#8 - 1300 MCM	1/4 - 1
FNXR-0420-2B-AL	2	2	3/8	#4 - 500 MCM	1/4 - 3/8
FNXR-39-2B-AL	2	2	1/2	350 - 1500 MCM	1/2 - 1
FNXR-39-4A-AL	1	3	1/2	350 - 1500 MCM	1/2 - 1
FNXR-48-4A-AL	1	3	3/4	#2 - 2000 MCM	3/8 - 1
FNXR-48-4B-AL	1	4	3/4	#2 - 2000 MCM	3/8 - 1